

DIAGNOSTIC SYSTEM COMPARISON



MaxiDAS® DS708



MaxiSYS® Mini



MaxiSYS™



MaxiSYS™ Pro

	MaxiDAS® DS708	MaxiSYS® Mini	MaxiSYS™	MaxiSYS™ Pro
CPU	Samsung S3C2440 ARM9 Processor 400 MHZ	Samsung Exynos Quad-Core Processor 1.4GHz	Samsung Exynos Quad-Core Processor 1.4GHz	Samsung Exynos Quad-Core Processor 1.4GHz
OS	Windows CE	Android 4.0 Ice Cream Sandwich	Android 4.0 Ice Cream Sandwich	Android 4.0 Ice Cream Sandwich
SSD Hard Drive		32 GB	32 GB	32 GB
Touch Screen Display	7.0" 800×480 TFT Resistive Touch Screen	7.9" 1,024 x 768 LED Capacitive Touch Screen	9.7" 1,024 x 768 LED Capacitive Touch Screen	9.7" 1,024 x 768 LED Capacitive Touch Screen
Connectivity	USB 2.0; Ethernet Wi-Fi;	USB 2.0; Wi-Fi; Bluetooth	USB 2.0; Ethernet; Wi-Fi; Bluetooth	USB 2.0; Ethernet; Wi-Fi; Bluetooth
Dual Band 802.11n Wi-Fi	2.4GHz	2.4GHz & 5GHz	2.4GHz & 5GHz	2.4GHz & 5GHz
Internal Battery		5000 mAh 3.7V Lithium Polymer Battery	11000 mAh 3.7V Lithium Polymer Battery	11000 mAh 3.7V Lithium Polymer Battery
Weight (Display)	2.95lb (1.1kg)	1.54lb (0.70kg)	3.12lb (1.42KG)	3.12lb (1.42KG)
Camera (rear)		5.0 Megapixel, AF with Flashlight	5.0 Megapixel, AF with Flashlight	5.0 Megapixel, AF with Flashlight
Wireless VCI		●	●	●
Optional lab Scope		●	●	●
Optional VideoScope		●	●	●
Boot Up Time	40 Seconds	20 Seconds	20 Seconds	20 Seconds
Complete OEM-Specific Scanner Coverage	●	●	●	●
AutoVIN Technology		●	●	●
MaxiFix Cloud-Based Information System		●	●	●
Shop Manager		●	●	●
ECU Coding	Minimum	Advanced	Advanced	Advanced
ECU Flash Programming				●
Subscription-Based On-Line Updates	●	●	●	●
J2534 Hardware Included				●